

Self-Propelled Scissor Lifts

GS™ -2669 DC, GS-3369 DC, GS-4069 DC

Features

Standard Features	Easily Configured To Meet Your Needs	Options & Accessories
<p>Measurements</p> <p>GS-2669 DC</p> <ul style="list-style-type: none"> • 9.70 m (31 ft 9 in) working height • Up to 680 kg (1,500 lbs) lift capacity <p>GS-3369 DC</p> <ul style="list-style-type: none"> • 11.75 m (38 ft 6 in) working height • Up to 454 kg (1,000 lbs) lift capacity <p>GS-4069 DC</p> <ul style="list-style-type: none"> • 14.12 m (46 ft 3 in) working height • Up to 363 kg (800 lbs) lift capacity <p>Productivity</p> <ul style="list-style-type: none"> • Drive at full height • AC sealed drive motors • Folding guardrails with full height swing-gate • Smart Link™ control system (joystick, 2 lift speeds & 2 selectable proportional drive speeds, user-friendly diagnostics) • Platform control with battery charge indicator and diagnostic display • On-board diagnostic system • AC power to platform • Front oscillating axle • Positive traction control • Regenerative braking • Tilt level sensor with audible alarm • Descent alarm • Flashing LED beacons • Horn • Hour meter • Telematics-Ready Connector <p>Power</p> <ul style="list-style-type: none"> • 48 V DC battery pack 	<p>Platform</p> <ul style="list-style-type: none"> • 2.79 x 1.60 m (9 ft 2 in x 5 ft 3 in) steel frame platform with replaceable aluminium deck • 1.52 m (5 ft) slide-out extension deck <p>Outrigger Options</p> <ul style="list-style-type: none"> • Automatic levelling hydraulic outriggers⁽¹⁾ • No outriggers (standard) <p>Power Options</p> <ul style="list-style-type: none"> • 48 V DC (eight 6 V batteries), 225 Ah (standard on GS-2669 DC & GS-3369 DC) • 48 V DC (eight 6 V batteries), 315 Ah (standard on GS-4069 DC) <p>Drive</p> <ul style="list-style-type: none"> • 2 x 4 <p>Axle</p> <ul style="list-style-type: none"> • Front oscillating axle <p>Tyres</p> <ul style="list-style-type: none"> • Foam-filled, non-marking rough terrain 	<p>Productivity Options</p> <ul style="list-style-type: none"> • Air line to platform • Power to platform plug, socket with optional Residual-current Circuit Breaker with Overcurrent protection • Biodegradable hydraulic oil • Track & Trace ⁽¹⁾ (GPS unit providing machine location & operating information) • Motion alarm <p>Power Options</p> <ul style="list-style-type: none"> • Low temperature cut-out module • 48 V DC (eight 6 V batteries), 315 Ah - on GS-2669 DC & GS-3369 DC

⁽¹⁾ Includes a first 2 years subscription



01/18 Part No. B127292UK

United Kingdom

The Maltings, Wharf Road, Grantham NG31 6BH, T: +44 800 988 3739 (toll free), Fax +44 (0)1476 584334, Email AWP-InfoEurope@terex.com
Visit www.genielift.co.uk/locations to view our global locations list.

Worldwide Manufacturing And Distribution

Australia · Brazil · Caribbean · Central America · China · France · Germany · Italy · Japan · Korea · Mexico · Russia · Southeast Asia · Spain · Sweden · United Arab Emirates · United Kingdom · United States

Product specifications and prices are subject to change without notice or obligation. The photographs and/or drawings in this document are for illustrative purposes only. Refer to the appropriate Operator's Manual for instructions on the proper use of this equipment. Failure to follow the appropriate Operator's Manual when using our equipment or to otherwise act irresponsibly may result in serious injury or death. The only warranty applicable to our equipment is the standard written warranty applicable to the particular product and sale and we make no other warranty, express or implied. Products and services listed may be trademarks, service marks or trade names of Terex Corporation and/or their subsidiaries in the USA and many other countries. Genie is a registered trademark of Terex South Dakota, Inc. © 2018 Terex Corporation.

